

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/29/2026

Version No. 1

Reviewed on 07/29/2026

1 Identification

- **Trade name:** UZIN NC 888 MT
- **Sector of Use** For professional use only.
- **Uses advised against:** No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Uzin Utz North America Inc.
 14509 E. 33rd. Place, Unit G
 Aurora, CO 80011
 Phone: +720-374-4810
 Toll-Free: +1 866-505-4810
 Fax: +1 720-374-2113
- **Information department:**
 Product safety department
 Phone: +720-373-4810
 email: safety.us@uzin-utz.com
- **Emergency telephone number:**
 For Chemical Emergency Spill Leak Fire Exposure or Accident
 Call CHEMTREC Day or Night: DOMESTIC NORTH AMERICA 800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carcinogenicity 1A

H350 May cause cancer. Route of exposure: Inhalation.

Specific target organ toxicity (repeated exposure) 1 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.



GHS05 Corrosion

Eye damage 1

H318 Causes serious eye damage.



GHS07

Skin irritation 2

H315 Causes skin irritation.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**
 Portland cement

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/29/2026

Version No. 1

Reviewed on 07/29/2026

Trade name: UZIN NC 888 MT

(Contd. of page 1)

*Quartz (crystalline silica)***· Hazard statements***Causes skin irritation.**Causes serious eye damage.**May cause cancer. Route of exposure: Inhalation.**Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.***· Precautionary statements***Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Do not breathe dust.**Wear protective gloves/protective clothing/eye protection/face protection.**If on skin: Wash with plenty of soap and water.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.**Continue rinsing.**IF exposed or concerned: Get medical advice/attention.**If eye irritation persists: Get medical advice/attention.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***· Additional information:** *Restricted to professional users.***· Information pertaining to particular dangers for man and environment:****· NFPA ratings (scale 0 - 4)***Health = 2**Flammability = 0**Reactivity = 0***· HMIS-ratings (scale 0 - 4)***Health = 2**Flammability = 0**Reactivity = 0***· Other hazards***NFPA Rating Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe.**NFPA is the National Fire Protection Association.**HMIS Rating Scale: 0 = Minimal; 1 = Slight; 2 = Moderate; 3 = Serious; 4 = Severe.**HMIS®, the Hazardous Materials Identification System, is a registered mark of the National Paint and Coatings Association (NPCA).*** Chronic health effect possible - inhalation of silica dust may cause lung injury/disease (silicosis). Take appropriate measures to avoid breathing dust. See sections 3, 8 and 11.***· Classification according to (d)(1)(ii) of § 1910.1200***The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.***· Hazards not otherwise classified***There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.*

3 Composition/information on ingredients

· Chemical characterization: Mixtures**· Description:** *Mixture of the substances listed below with nonhazardous additions.*

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/29/2026

Version No. 1

Reviewed on 07/29/2026

Trade name: UZIN NC 888 MT

(Contd. of page 2)

· Hazardous ingredients:		
CAS: 26499-65-0	Calcium sulfate	10-30%
CAS: 65997-15-1	Portland cement	5-<20%
	⚠ Eye damage 1, H318; ⚠ Skin irritation 2, H315; Specific target organ toxicity (single exposure) 3, H335	
CAS: 14808-60-7	Quartz (crystalline silica)	0.1-1%
	☠ Carcinogenicity 1A, H350; Specific target organ toxicity (repeated exposure) 1, H372	

· Additional information:

The exact percentages of the ingredients have been withheld by the manufacturer as trade secrets.
For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Description of first aid measures

· General information: No special measures required.

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

If eye irritation persists: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing: Do not induce vomiting; immediately call for medical help.

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO₂ extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

· Special hazards arising from the substance or mixture No further relevant information available.

· Advice for firefighters

· Protective equipment: Wear dust mask.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Wear dust mask.

Avoid formation of dust.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Pick up mechanically.

Do not flush with water or aqueous cleansing agents

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/29/2026

Version No. 1

Reviewed on 07/29/2026

Trade name: UZIN NC 888 MT

(Contd. of page 3)

· Protective Action Criteria for Chemicals

· PAC-1:

CAS: 14808-60-7	Quartz (crystalline silica)	0.075 mg/m ³
CAS: 554-13-2	lithium carbonate	1.0 mg/m ³
CAS: 1309-48-4	magnesium oxide	2.4 mg/m ³

· PAC-2:

CAS: 14808-60-7	Quartz (crystalline silica)	8.3 mg/m ³
CAS: 554-13-2	lithium carbonate	11 mg/m ³
CAS: 1309-48-4	magnesium oxide	130 mg/m ³

· PAC-3:

CAS: 14808-60-7	Quartz (crystalline silica)	50 mg/m ³
CAS: 554-13-2	lithium carbonate	68 mg/m ³
CAS: 1309-48-4	magnesium oxide	750 mg/m ³

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Prevent formation of dust.

Wear suitable protective clothing, gloves and eye/face protection.

Avoid contact with the eyes and skin.

When mixing wear suitable NIOSH-approved dust respirator.

Provide appropriate exhaust ventilation at places where airborne dust is generated. In case of insufficient ventilation, wear suitable respiratory protective equipment (e.g. NIOSH-approved dust respirator).

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Information about protection against explosions and fires: No special measures required.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: Keep receptacle tightly sealed.

· Information about storage in one common storage facility: Store away from foodstuffs.

· Further information about storage conditions:

Store in dry conditions.

Protect from humidity and water.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 26499-65-0 Calcium sulfate	
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/29/2026

Version No. 1

Reviewed on 07/29/2026

Trade name: UZIN NC 888 MT

(Contd. of page 4)

REL	Long-term value: $10 \times 5^{**} \text{ mg/m}^3$ *total dust **respirable fraction
CAS: 65997-15-1 Portland cement	
PEL	Long-term value: 50 mppcf or $15 \times 5^{**} \text{ mg/m}^3$ *total dust **respirable fraction
REL	Long-term value: $10 \times 5^{**} \text{ mg/m}^3$ *total dust **respirable fraction
TLV	Long-term value: $1 \times \text{mg/m}^3$ E; *as respirable fraction, A4
CAS: 14808-60-7 Quartz (crystalline silica)	
PEL	Long-term value: $0.05 \times \text{mg/m}^3$ *resp. dust; $30 \text{ mg/m}^3 / \% \text{SiO}_2 + 2$
REL	Long-term value: $0.05 \times \text{mg/m}^3$ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: $0.025 \times \text{mg/m}^3$ *respirable particulate matter, A2

Regulatory information

PEL: Guide to Occupational Exposure Values (OSHA PELs)
REL: Guide to Occupational Exposure Values (NIOSH RELs)
TLV: Guide to Occupational Exposure Values (TLV)

Exposure controls

Appropriate engineering controls

Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product.

Personal protective equipment:

General protective and hygienic measures:

Prevent formation of dust.
Avoid contact with the eyes and skin.
Wear suitable protective clothing, gloves and eye/face protection.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.

Respiratory protection:

When mixing wear suitable NIOSH-approved dust respirator.
Provide appropriate exhaust ventilation at places where airborne dust is generated. In case of insufficient ventilation, wear suitable respiratory protective equipment (e.g. NIOSH-approved dust respirator).

Protection of hands:



Use nitrile impregnated cotton-gloves

Material of gloves

Nitrile impregnated cotton-gloves
Recommended thickness of the material: 0,15 mm

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
At least 480 minutes.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/29/2026

Version No. 1

Reviewed on 07/29/2026

Trade name: UZIN NC 888 MT

(Contd. of page 5)

· Eye protection:



Safety glasses

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Physical state	Solid
· Color:	Gray
· Odor:	Light
· Odor threshold:	Not determined
· Melting point/Melting range:	Undetermined
· Boiling point/Boiling range:	Undetermined
· Flammability:	Not determined
· Explosion limits:	
· Lower:	Not determined
· Upper:	Not determined
· Flash point:	Not determined.
· Decomposition temperature:	Not determined
· pH-value at 20 °C (68 °F):	~11
· Kinematic	
· Dynamic:	Not applicable
· Solubility in / Miscibility with	
· Water:	Sets with water.
· Partition coefficient (n-octanol/water):	Not determined
· Vapor pressure:	Not applicable
· Vapor pressure:	
· Density:	Not determined
· Relative density	Not determined
· Vapor density	Not applicable
· Particle characteristics	Not determined

· Other information

· Appearance:	
· Form:	Solid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· VOC-content:	
· Solids content:	100.0 %
· Change in condition	
· Evaporation rate	Not applicable.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under normal conditions.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/29/2026

Version No. 1

Reviewed on 07/29/2026

Trade name: UZIN NC 888 MT

(Contd. of page 6)

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· **Primary route(s) of entry:** Inhalation, skin contact, eye contact.

· Primary irritant effect:

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Strong irritant with the danger of severe eye injury.

· Sensitization:

No sensitizing effects known.

Low in Chromate (< 2 ppm) acc. Regulation (EC) No 1907/2006 (REACH).

· Subacute to chronic toxicity:

This product contains crystalline silica. Crystalline silica (respirable size) is classified as carcinogenic by inhalation by IARC (Group 1), ACGIH (Group A2), NTP (Group 1) and OSHA (OSHA Select carcinogen). Respirable crystalline silica may cause a severe lung disease named silicosis. Symptoms of silicosis may be a shortness of breath, fever or cough. Silicosis is reported to increase the risk of carcinogenicity caused by continuous inhalation of respirable crystalline silica. Respirable silica may be generated from working procedures such as grinding. In general, inhalation of silica dust should be avoided. Therefore, for your own safety comply with all requirements within OSHA Standard 29 CFR § 1926.1153 - Respirable crystalline silica for Construction.

· **Additional toxicological information:** Carcinogenic.

· **Interactive effects** No interactive effects between components are known.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 14808-60-7 Quartz (crystalline silica)

I

· NTP (National Toxicology Program)

CAS: 14808-60-7 Quartz (crystalline silica)

K

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Alternative sources for toxicological information

No non-standard sources for toxicological information where used.

· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity 1A

· Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

· Toxicity

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Bioaccumulative potential** No further relevant information available.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/29/2026

Version No. 1

Reviewed on 07/29/2026

Trade name: UZIN NC 888 MT

(Contd. of page 7)

- **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
- **PBT:**
This substance/mixture does not contain any components that can be considered persistent, bioaccumulative and toxic (PBT).
- **vPvB:**
This substance/mixture does not contain any components that can be considered very persistent and very bioaccumulative (vPvB) at levels of 0.1%.
- **Other adverse effects**
- **Additional ecological information:**
- **General notes:** Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Do not allow product to reach sewage system.
Mix product residues with water, allow to harden, then dispose of as construction waste.
- **Uncleaned packagings:**
- **Recommendation:** Empty paper packaging is recyclable.

14 Transport information

- **DOT, ADR, IMDG, IATA** Void
- **UN proper shipping name**
- **DOT, ADR, IMDG, IATA** Void
- **DOT, ADN, IMDG, IATA**
- **Class** Void
- **DOT, IMDG, IATA** Void
- **Environmental hazards:** Not applicable
- **Special precautions for user** Not applicable
- **UN "Model Regulation":** Void

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **SARA (Superfund Amendments and Reauthorization Act)**

· **EPCRA Section 302 (Extremely Hazardous Substances):**

None of the ingredient is listed.

· **SARA Title III Section 313 (Toxic Release Inventory - TRI):**

CAS: 554-13-2 | lithium carbonate

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

All components have the value ACTIVE.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 07/29/2026

Version No. 1

Reviewed on 07/29/2026

Trade name: UZIN NC 888 MT

(Contd. of page 8)

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65 (California)
· Chemicals known to cause cancer:

CAS: 14808-60-7 Quartz (crystalline silica)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 554-13-2 lithium carbonate

· Carcinogenicity categories
· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

CAS: 14808-60-7 Quartz (crystalline silica)

A2

CAS: 1309-48-4 magnesium oxide

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 14808-60-7 Quartz (crystalline silica)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

· Contact:

Product safety department

phone: +720-373-4810

email: safety.us@uzin-utz.com

· Date of previous version 07/29/2026
· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Date of issue: 07/29/2026

Version No. 1

Reviewed on 07/29/2026

Trade name: UZIN NC 888 MT

(Contd. of page 9)

*TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**Skin irritation 2: Skin corrosion/irritation – Category 2**Eye damage 1: Serious eye damage/eye irritation – Category 1**Carcinogenicity 1A: Carcinogenicity – Category 1A**Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3**Specific target organ toxicity (repeated exposure) 1: Specific target organ toxicity (repeated exposure) – Category 1*

US